INDEX

RUBBER CHEMISTRY AND TECHNOLOGY

VOLUME 42, 1969

AUTHOR INDEX

ABE, Y., see SHIMANOUCHI, J., (5) 1383
ABOYTES, P., see PRICE, C. R., (2) 598
ALTENAU, A. G., see TURNER, R. R., (4) 1054
AMBELANG, J. C., F. H. WILSON, JR., L. E. PORTER, AND D. L. TURK, Ozone crack initiation: statistical and deterministic interpretations of the action of p-phenylenediamines and EPDM as antiozonants, (4) 1186
ANDERSON, J. N., F. C. WEISSERT, AND C. J. HUNTER, Thermal analysis of butadiene styrene block copolymers, (3) 918
ANDREWS, E. H., AND P. E. REED, Hydrogen evolution from natural rubber during tensile tests, (2) 505
ANDREWS, R. D., see HAMMACK, T. J., (2) 509
ASHIKARI, N., I. KAWASHIMA, AND T. KAWASHIMA, Dependence of the crosslinking efficiency on the reaction conditions in the peroxide crosslinking of unsaturated polyolefins, (5) 1245
ATKINS, J. H., AND J. E. SULLIVAN, JR., Apparatus to measure thermal conductivity in filled rubber stocks, (5) 1314

BALDWIN, F. P., P. BORZEL, AND H. S. MAKOWSKI, The correlation between entanglement and chemical crosslinks in EPDM vulcanizates, (4) 1167
BAN, L. L., see HESS, W. M., (4) 1209
BANDERET, A., see RIESS, G., (2) 447
BANERJEE, S., see MANIK, S. P., (3) 744
——, see BHATNAGAR, S. K., (5) 1366
BARANWAL, K., Effect of compounding on autohesion of rubbers (Abstract), (5) 1480
BARTON, F. W., see BRENNER, F. C., (5) 1462
BEATTY, J. R., Tel-tak: A mechanical method for estimating both tackiness and stickiness of rubber compounds, (4) 1040
BECKER, G. W., AND H. J. RADEMACHER, Viscoelastic behavior of high polymers at large deformations, (2) 373
BERNETT, B., see MUELLER, W. J., (3) 966
BENOIT, H., see GRUBISIC, Z., (2) 636
BERGSTROM, E. W., see OSSEFORT, Z. T., (3) 975
BHATNAGAR, S. K. AND S. BANERJEE, Kinetics of accelerated vulcanization. III. N-cyclohexyl-benzothiazole-2-sulfenamide accelerated sulfur vulcanization of rubbers, (5) 1366
BIALAS, G. A., AND J. L. WHITE, Extrusion of polymer melts and melt flow instabilities. I. Experimental study of capillary, (3) 675
——, Extrusion of polymer melts and melt flow instabilities. II. Site of initiation and mechanism of melt flow, (3) 682
BLYLER, L. L., JR., Some aspects of the relationship between molecular structure and flow behavior of polymer melts, (3) 823
BORZEL, P., see BALDWIN, F. P., (4) 1167
BOYER, J. S., see DIMELER, G. R., (5) 1474
BREE, H. W., see SCHWARZL, F. R., (2) 557
BRENNER, F. C., Research for a uniform quality grading system for tires, (5) 1446
——, J. MANDEL, AND B. G. SIMSON, Research for a uniform grading system for tires. II. Wheel speed capability test, (5) 1450
——, AND F. W. BARTON, Cuts and cut growth in tires, (5) 1462
BRISTOL, K. E., see SINCLAIR, E. A., (5) 1476
BROWN, J. E., JR., see LIVINGSTON, D. I., (4) 1014
BSHARAH, L., see MAY, W. R., (5) 1468

CAMPBELL, D. R., AND W. C. WARNER, Radioisotope methods of analysis and characterization of elastomers (Review), (1) 1
CHAPPELL, S. F., III, see FORRESTER, R. A., (3) 957
CHASSET, R., see LANGLEY, N. R., (5) 1277
CHEN, HUNG YU, AND J. E. FIELDS, Configuration of isoprene structure in butyl rubber by time–averaging high resolution nuclear magnetic resonance, (2) 392
CHILDERS, C. W., see KRAUS, G., (2) 520
CHIRICO, V., see SCOTT, C. E. (3) 700
COLCLOUGH, T., J. I. CUNEEN, AND G. M. C. HIGGINS, Oxidative aging of natural rubber vulcanizates. III. Crosslink scission in monosulfidic networks, (3) 924
COLLIER, J. R., Polymer crystallization history and resultant properties, (3) 769
COLLINS, E. A., AND J. T. OETZEL, Rheological behavior of elastomers. I. Melt viscosity characteristics of uncured epichlorohydrin rubber, (3) 790
——, Rheological behavior of elastomers. II. Effect of filler type and level on the flow characteristics of hydrin and related rubbers (Abstract), (5) 1487
COOPER, S. L., D. S. HUH, AND W. J. MORRIS, Stress softening in crosslinked block copolymer elastomers (Abstract), (3) 956
COOPER, W. T., see HAWS, J. R., (5) 1495

CORMAN, B. G., M. L. DEVINEY, JR., AND L. E. WHITTINGTON, The migration of extender oil in natural and synthetic rubber. IV. Effect of saturates geometry, carbon black type, and dynamic conditions on diffusion rates (Abstract), (5) 1473
CORMAN, B. G., see LEWIS, J. E., (2) 474
COTTEN, G. R., Die Swell of filled rubbers (Abstract), (3) 957
COWING, G. S., AND T. A. KNUREK, The present needs and future trends of automotive hose (Abstract), (3) 982
CROCKER, G. J., Elastomers and their adhesion (Review), (1) 30
CUNEEN, J. I., see COLCLOUGH, J., (3) 924
CUNNINGHAM, R. E., Course of the terpolymerization of ethylene, propylene, and dicyclopentadiene. I. Single addition of dicyclopentadiene, (2) 363
——, Course of the terpolymerization of ethylene, propylene, and dicyclopentadiene. II. Two-step addition of dicyclopentadiene, (2) 368

DALL' ASTA, G., AND P. SCAGLIONE, All-*cis* polypentenamer: a potential new elastomer for low-temperature applications, (5) 1235
DAUGHERTY, J. P., AND J. T. KEHN, Unique EPDM polymer for hose applciations (Abstract), (3) 980
DAVISON, L., Meeting papers abstracts, (3) 956, (5) 1466
DE BRUYNE, E., see MAESCELE, A., (2) 613
DE PIERRI, W. G. JR., AND J. R. HOPPER, Effect of oil and black on the injection molding of EPDM compounds, (5) 1321
——, Effect of oil and black on the injection molding of EPDM compounds. II. Molding studies, (5) 1336
DEASON, W. R., AND R. W. WISE, Programmed temperature curemetry (Abstract), (5) 1481
DERRINGER, G. C., Predicting properties with accuracy (Abstract), (5) 1469
DEVINEY, M. L., JR., see LEWIS, J. E., (2) 474, (3) 892
——, see CORMAN, B. G., (5) 1473
DICKIE, R. A., see SMITH, T. L., (5) 1257
——, see LANGLEY, N. R., (5) 1277
DIMELER, G. R., J. S. BOYER, AND I. W. MILLS, Oil requirements of various EPDM rubbers. II. The impact of polar compounds (Abstract), (5) 1474

EDWARDS, C. H., Mixing from a processing and equipment point of view (Abstract), (5) 1492
EICHINGER, B. E., AND P. J. FLORY, Determination of the equation of state of polyisobutylene, (5) 1409
——, see FLORY, P. J., (5) 1397
ELLENSON, J. L., see FLORY, P. J., (5) 1397
EVANS, C. W., The manufacture of hose in Europe (Abstract), (3) 984
——, European mixing techniques (Abstract), (5) 1492
FAVRE, J. P., Study of 2-mercaptobenzothiazole-zinc compounds and their development during aging of rubber vulcanizates. II. Development during aging of rubber vulcanizates, (3) 735
FEDORS, R. F., AND R. F. LANDEL, A test of the predictability of filled systems (Abstract), (5) 1498
——, see MOACANIN, J. (5) 1501
FENSTERMAKER, C. A., see SMITH, J. C. (2) 565
FERRY, J. D., see LANGLEY, N. R., (5) 1277
FIELDS J. E., see CHEN, HUNG YU, (2) 392
FISCHER, W. F., Profile vulcanization. A new method for measuring the total vulcanization history of elastomers (Abstract), (3) 968
FLORY, P. J., J. L. ELLENSON, AND B. E. EICHINGER, Thermodynamics of mixing of n-alkanes with polyisobutylene (5) 1397
——, see EICHINGER, B. E., (5) 1409
FOLT, V. L., The effects of mechanical degradation on rheological properties of elastomers, (5) 1294
FORRESTER, R. A., AND S. F. CHAPPELL, III The effects of coagulation conditions and black dispersions on processibility and properties of SBR masterbatch (Abstract), (3) 957
FORSTER, M. J., AND I. B. PRETTYMAN, A new improved tirecord fatigue tester, (4) 1000
FRASER, C. R. see MONTAG, R. J., (5) 1491
FRENCH, D. M. Functionally terminated butadiene polymers (Review), (1) 71
FUGE, C., see HUMMEL, K., (2) 471
FUJIMOTO, K. see SEKIGUCHI, H., (2) 547
——, see YOSHIMURA, N., (4) 1009

GAETA, L. J., see TURNER, R. R., (4) 1054
GARDINER J. B., Measurement of curative diffusion between rubbers by microinterferometry, (4) 1058
GATZA, P. E., see MITTON, P., (3) 964
GEHMAN, S. D., Network chain distribution and strength of vulcanizates, (3) 659
——, (4) G 97
—— see MAVRIGIAN, G., (4) 1034
GESCHWIND, D. H., Ram injection molding of elastomers. Factors affecting clamp time (Abstract), (3) 959
GESSLER, A. M., Evidence for chemical interaction in carbon and polymer associations. Butyl and acidic oxy blacks. The possible role of carboxylic acid groups on the black, (3) 850
——, Evidence for chemical interaction in carbon and polymer associations. II. Extension of original work of effect of carbon black structure, (3) 858
—— The anatomy of bound rubber (Abstract), (5) 1494
GIVEN, P. H., see PAPIRER, E., (4) 1200
GOODSTEIN, S. J., see YOUNG, D. G., (3) 973
GOSHORN T. R., A. H. JORGENSEN, AND M. E. WOODS, Powdered rubber technology. I. Processing of powdered NBR compounds (Abstract), (5) 1478
GRAHAM, T. L., Thermally stable triazine elastomer vulcanizates (Abstract), (3) 963
GREGG, E. C. JR., Sulfur crosslinks in polybutadiene vulcanizates, (4) 1136
GRUBISIC, Z., P. REMPP, AND H. BENOIT, A universal calibration for gel permeation chromatography, (2) 636
GRUVER, J. T., see KRAUS, G., (2) 520
——, see KRAUS, G., (3) 800
GURGIOLO, A. E., Preparation of epoxide rubber containing allylic chloride, (4) 1028

HAMMACK, T. J., AND R. D. ANDREWS, Temperature dependence of orientation birefringence in rubber and semicrystalline polymers, (2) 509
HARKLEROAD, W. I., Basic principles of hose design, (3) 666
HAWS, J. R., C. R. WILDER, AND W. T. COOPER, Effect of carbon black structure on abrasion resistance (Abstract), (5) 1495
HEATH, A. B., see NEY, E. A. (5) 1350
HEGMON, R. R., The contribution of deformation losses to rubber friction, (4) 1122
HERSHEY, J. S., Polymers for present day hose (Abstract), (3) 982
HESS, W. M., L. L. BAN, AND G. C. MCDONALD, Carbon black morphology: I. Particle microstructure. II. Automated EM analysis of aggregate size and shape, (4) 1209
HIGGINS, G. M. C., see COLCLOUGH, T. (3) 924
HILL, R. W., see PATTLE, R. E., (2) 481
HOEHNE, K., The curing of polyisoprene coating materials with polyisocyanates, (2) 394
HOFTYZER, P. J., see VAN KREVELEN, D. W. (2) 462
HOPPER, J. R., see DE PIERRI, W. G., JR., (5) 1321
HUDSON R. W. A., see WILLIAMS, R. J., (2) 641
HUH, D. S., see COOPER, S. L., (3) 956
HUMMEL, K., AND C. FUGE, Extraction of low molecular weight materials from gel spherules using the system: benzoic acid/cyclohexane/crosslinked polyisoprene, (2) 471
HUNTER C. J., see ANDERSON, J. N., (3) 918

INO, H., M. TSUKASA, T. NAGAFUNE, K. K. SEKARCHO, AND Y. MINOURA, Studies on blended polymers. VIII. Blending of carboxy SBR and vinylpyridine SBR, (3) 759

JACKSON, J. L. see SHEN, M. C., (3) 835
JACOBS, H. L., Mixing from a compounders point of view (Abstract), (5) 1492
JENKINS, R. C., see MONTAG, R. J., (5) 1491
JONES W. B., JR., A simple test for certain cases of adhesion (Abstract), (5) 1486
JORGENSEN, A. H., see GOSHORN, T. R., (5) 1478

KAKIUCHI, M., see SEKIGUCHI, H., (2) 547
KANAVEL G. A., M. P. MAZZEO, AND J. J. SCHULTHEIS, Improved low temperature and water resistances for millable polyester urethans Abstract), (5) 1502
KAWASHIMA, I., see ASHIKARI, N., (5) 1245
KAWASHIMA, T., see ASHIKARI, N. (5) 1245
KEHN, J. T., see DAUGHERTY, J. P. (3) 980
KELLEY, F. N., AND M. L. WILLIAMS, The engineering of polymers for mechanical behavior (4) 1175
KERWOOD, J. E., R. I. LEIB, AND C. D. TRIVETTE, JR., Sulfenamide accelerated sulfur vulcanization of black filled natural rubber (Abstract), (3) 969
KLEIN I., see TADMOR, Z., (3) 780
KIM, C. S., Important mechanical and chemical factors in the failure behavior of polybutadiene rubber undergoing oxidative aging at ambient temperatures, (4) 1095
KNUREK, T. A., see COWING, G. S., (3) 982
KOCH, R. W., see TURNER, R. R., (4) 1054
KOHLER, J., see RIESS, G., (2) 447
KOKOROPOULOS, P., Comments on the significance and use of a centralized information facility on high polymers (Abstract), (5) 1490
KRAUS G., C. W. CHILDERS, AND J. T. GRUVER, Properties of random and block copolymers of butadiene and styrene. I. Dynamic properties and glassy transition temperatures, (2) 520
——, AND J. T. GRUVER, The viscosity of carboxy-terminated polybutadienes, (3) 800
——, see WALDROP, M. A., (4) 1155

LAL, J The effect of crosslink structure on the tensile strength and oxygen absorption characteristics of natural rubber vulcanizates, (5) 1412
LANDEL, R. F., see FEDORS, R. F., (5) 1498
——, see MOACANIN, J. (5) 1501
LANGLEY, N. R., R. A. DICKIE, CHIU-PING WONG, J. D. FERRY, R. CHASSET, AND P. THIRION, Low frequency losses in rubbers crosslinked in the presence of diluent, (5) 1277
——, Elastically effective strand density in polymer networks (5) 1285
LATOS, E. J., AND A. K. SPARKS, Parameters affecting extractability of p-phenylenediamine antiozonants from rubber stocks with water (Abstract), (5) 1471
LEEMING, H., A review of certain techniques for vicsoelastic materials (Abstract), (5) 1487
LEIB R. I., see KERWOOD, J. E., (3) 969
LEIBEE, J. B. AND W. J. SCHAFFERS, A new tire expansion rule and its use in tire design computations, (4) 1079
LEO, T. J., Review of recent advances in hose making equipment (Abstract), (3) 983
LEWIS, J. E., M. L. DEVINEY JR., B. G. CORMAN, The migration of extender oil in natural and synthetic rubber. III. Relative contributions of principal structures in aromatic fractions to diffusion, (2) 474
———, L. E. WHITTINGTON, Migration of antioxidants and accelerators in natural and synthetic rubber. II. Sulfenamide system studies and comparison of age resister migration under inert and practical conditions, (3) 892
LIVINGSTON, D. I., AND J. E. BROWN JR., Physics of the slipping wheel. I. Force and torque calculations for various pressure distributions, (4) 1014
LIVINGSTON, H. K., AND G. P. REGHI, An internally consistent thermodynamics for elastomers, (2) 441

MCDONALD, G. C., see HESS, W. M., (4) 1209
MCQUARRI, D. A., see SHEN, M. C., (3) 835
MAESEELE, A., AND E. DE BRUYNE, Problems concerning adhesion of steel wire and steel cord in rubber (2) 613
MAIER, J. E., K. U. PATEL, AND D. A. STIVERS, A new low compression set elastomer (Abstract) (5) 1503
MAKOWSKI, H. S., see BALDWIN, F. P. (4) 1167
MANDEL, J., see BRENNER, F. C., (5) 1450

MANIK, S. P., AND S. BANERJEE, Studies on dicumyl peroxide vulcanization of natural rubber in presence of sulfur and accelerators, (3) 744
MARTIN, R. A., AND K. C. PETERSEN, Phenolic antioxidant with new and unusual properties (Abstract), (5) 1466
MATSUI, J., see TAKEYAMA, J., (1) 159
MAURER J. J., Application of differential thermal analysis and thermogravimetric analysis to elastomer systems (Review) (1) 110
MAURER, J. J., Thermal analysis of elastomer systems. IV. Carbon black analysis by TGA (Abstract), (5) 1490
MAVRIGIAN, G., AND S. D. GEHMAN, General method for approximating the tire contour integral for arbitrary cord path, (4) 1034
MAY W. R., AND L. BSHARAH, Oxidation of styrene–butadiene rubber catalyzed by metallic ions (Abstract), (5) 1468
MAZZEO, M. P., see KANAVEL, G. A., (5) 1502
MEDALIA, A. I., Morphology of aggregates. IV. Effective volume of aggregates from electron microscopy: application to DBP absorption and extrusion shrinkage (Abstract), (5) 1496.
MEIER, D. J., see MITCHELL, J. C., (5) 1420
MERZ, P. L., Fluorocarbon elastomers as potential seal rubbers for aerospace vehicles. I. Commercial fluorocarbon rubber O-rings (Abstact), (5) 1502
MILLS I. W., see DIMELER, G. R., (5) 1474
MINOURA, Y., see IINO, H., (3) 759
MITCHELL, J. C., Mechanical history effects in the crystallization of *cis*-1,4-polybutadiene (2) 530
——, AND D. J. MEIER, Rapid stress-induced crystallization in natural rubber, (5) 1420
MITTON, P. F. E. GATZA, AND P. TOUCHET, Low temperature and fuel resistance properties of epichlorohydrin ethylene oxide blend compounds (Abstract), (3) 964
MOACANIN, J., R. F. FEDORS, AND R. F. LANDEL, Viscoelastic behavior of elastomers undergoing aging (Abstract), (5) 1501
MOLLICA J. C., see SINGH, A., (2) 648
MONTAG, R. J., C. R. FRASER, AND R. C. JENKINS, Fiberglass fatigue testing (Abstract), (5) 1491
MORIMOTO, T., see SEKIGUCHI, H., (2), 547.
MORRIS, W. J., see COOPER, S. L., (3) 956
MUELLER, W. J. AND B. BENNETT, New gum rosin derivatives for improving building tack of rubber compounds (Abstract), (3) 966
——, see STICKNEY, P. B., (2) 604
MULLENS, T. J., see VOET A., (3) 874
MULLINS, L., Softening of rubber by deformation (Review), (1) 339

NAGAFUNE, T., see IINO H., (3) 759
NAGASAWA, K., AND K. OHTA, Identification of organic compounding ingredients in vulcanized rubbers by thin layer chromatography, (2) 625
NEDERVEEN, C. J. see SCHWARZL, F. R., (2) 557
NEY, E. A., AND A. B. HEATH, Analysis of tire tread rubbers by gas chromatography, (5) 1350
NINOMIYA, K., AND G. YASUDA Processibility of rubbers and usefulness of the Mooney viscometer, (3) 714

OETZEL, J. T., see COLLINS, E. A., (3) 790
——, see COLLINS E. A., (5) 1487
OHTA, K., see NAGASAWA, K., (2) 625
O'MAHONEY, J. F., JR. Low sulfur sulfenamide accelerator combinations for injection molding *cis*-1,4-polyisoprene (Abstract), (3) 961
OSSEFORT, Z. T., AND E. W. BERGSTROM, Ethylene propylene rubbers as antiozonants (Abstracts), (3) 975
OXLEY C. E., AND G. J. WILSON, A peroxide curing butyl, (4) 1147
OZER, A., AND E. G. PARTRIDGE, The effect of temperature of test on abrasion resistance by the Pico method, (4) 1087

PAPIRER, E., A. VOET, AND P. H. GIVEN, Transfer of labeled hydrogen between elastomers and carbon black (4) 1200
PARTRIDGE, E. G., see OZER, A., (4) 1087
PATEL, K. U., see MAIER, J. E., (5) 1503
PATTERSON, R. A., The measurement of cord tensions in tires, (3) 812
PATTLE, R. E., P. J. A. SMITH, AND R. W. HILL, Tracer diffusion in rubber and benzene mixtures and its relation to mutual diffusion (2) 481
PAULIN, D. A., A new concept in the vulcanization of nitrile rubber (Abstract), (5) 1468
PEELE, S. J., JR., The use of fibers in hose manufacturing (Abstract), (3) 982
PETERSEN, K. C., see MARTIN, R. A., (5) 1466
PETERSON, W. H., (4) G87
PORTER, L. E., see AMBELANG, J. C., (4) 1186
PRETTYMAN, I. B. see FORSTER, M. J., (4) 1000
PRICE, C. R., AND P. ABOYTES, Influence of carbon black structure on vulcanizate properties, (2) 598

RADEMACHER, H. J., see BECKER G. W., (2) 373
REED, P. E., see ANDREWS, E. H., (2) 505
REGHI, G. P., see LIVINGSTON H. K., (2) 441
REHNER, J., JR., AND P. E. WEI, Heterogeneity and crosslinking of elastomer blends. Investigations of chlorobutyl with highly unsaturated elastomers, (4) 985
REMPP, see GRUBISIC, Z., (2) 636
RESNIK, G. J., The influence of hose coupling design on hose performance (Abstract), (3) 983
RIESS, G., J. KOHLER, C. TOURNUT, AND A. BANDERET, Compatibility of copolymers with corresponding homopolymers, (2) 447
RIJKE, A. M., AND G. L. TAYLOR, Stress-strain behavior of swollen polymeric networks, (2) 572
ROBERTS, D. E., Recrystallization and melting of partially melted stark rubber, (2) 540
ROGERS, T. H., (4) G97
RUSSELL R. M., T. D. SKINNER, AND A. A. WATSON, EV systems for NR. II. Further development of curing systems and vulcanization properties, (2) 418

SCAGLIONE, P., see DALL' ASTA, G., (5) 1235
SCHAFFERS, W. J., see LEIBEE, J. B. (4) 1079
SCHULTHEIS, J. J., see KANAVEL, G. A., (5) 1502
SCHWARZL, F. R. H. W. BREE, C. J. NEDERVEEN, G. A. SCHWIPPERT, L. C. E. STRUIK, AND C. W. VAN DER WAL, Behavior of unfilled and filled rubbers in shear in the glass–rubber transition region, (2) 557
SCHWIPPERT, G. A., see SCHWARZL, F. R., (2) 557
SCOTT, C. E. AND V. CHIRICO, Performance of SBR and BR tread compounds as a function of carbon black dispersion, surface chemistry, and structure, (3) 700
SCOTT, R., see TOKITA, N., (3) 944
SEKARCHO K. K., see IINO, H., (3) 759
SEKIGUCHI, H., M. KAKIUCHI, T. MORIMOTO, K. FUJIMOTO, AND N. YOSHIMURA, Poisson's ratio for stretched vulcanized natural rubber, (2) 547
SHALLAMACH, A. Friction and frictional rise of wedge sliders on rubber, (5) 1433
SHEN, M. C., D. A. MCQUARRI, AND J. L. JACKSON, Thermoelastic behavior of natural rubber, (3) 835
SHIMANOUCHI, T., AND Y. ABE, Skeletal deformation vibrations and rotational isomerism of methyl butenes and methyl pentenes as model compounds of 1,4-polyisoprene, (5) 1383
SHUTTLEWORTH, R., Volume change measurements in the study of rubber–filler interactions, (3) 936
SIMSON, B. G. see BRENNER, F. C., (5) 1450
SINCLAIR, E. A. AND K. E. BRISTOL, Reinforcement ofasphalt and tar by elastomer addition (Abstract), (5) 1476
SINGH, A., L. WEISSBEIN, AND J. C. MOLLICA, Thermal stability of polyester *vs.* polyether-based urethans (2) 648
SIRCAR, A. K., see VOET, A., (3) 874
SKINNER, T. D., AND A. A. WATSON, E V Systems for N.R.I. The purpose of efficient vulcanization and development of curing systems, (2) 404
——, see RUSSELL, R. M., (2) 418
SMITH, D. A., Micromethod for estimation of the degree of crosslinking in elastomers from compression modulus of swollen vulcanizates, (2) 580
SMITH, J. C., AND C. A. FENSTERMAKER, Strain-wave propagation in strips of natural rubber subjected to high-velocity impact, (2) 565
SMITH, M. G. Some factors affecting the interpretation of the plasticity retention index—P. R. I., (2) 381
SMITH, P. J. A., see PATTLE, R. E., (2) 481
SMITH, R. W., Microhardness testing with a spherically-tipped cone indentor (Abstract), (5) 1483
SMITH T. L., AND R. A. DICKIE, Viscoelastic and ultimate tensile of styrene–butadiene–styrene block copolymers, (5) 1257
SOUTHERN, E., AND A. G. THOMAS, Diffusion of liquids in crosslinked rubbers, (2) 495
SPARKS, A. K., see LATOS, E. J. (5) 1471
SPERBERG, L. R., Force variation and tire wear (Abstract), (5) 1485
STANTON, J. L., Computerized physical testing of elastomers (Abstract), (5) 1482
STICKNEY, P. B., AND W. J. MUELLER, Influence of carbon black on swelling rate of polymer in filled vulcanizates, (2) 604
STIVERS, D. A., see MAIER J. E., (5) 1503
STRUIK, L. C. E., see SCHWARZL, F. R., (2) 557
STUDEBAKER, M. L., A chemist looks at some aspects of physical testing of rubber (Abstract), (5) 1485
SULLIVAN, J. E., JR., see ATKINS, J. H., (5) 1314

TADMOR, Z., AND I. KLEIN, The formulation of a mathematical model for plasticating screw extrusion, (3) 780
TAKEYAMA, J., AND J. MATSUI, Recent developments with tire cords and cord to rubber bonding (Review), (1) 159
TAYLOR, G. L., see RIJKE, A. M. (2) 572
THIRION, P., see LANGLEY, N. R., (5) 1277
THOMAS, A. G. see SOUTHERN, E., (2) 495
THOMAS, R. M., Early history of butyl rubber, (4) G 90
TOKITA, N., AND R. SCOTT, Rheological properties and molecular structure of elastomers: EPM, EPDM (3) 944
TOUCHET, P., see MITTON, P., (3) 964
TOURNUT C., see RIESS, G., (2) 447
TRELOAR, L. R. G., Effect of network breakdown and re-formation on the swelling of rubbers in compression, (2) 589
TRIVETTE, C. D., JR., see KERWOOD, J. E., (3) 969
TSUKASA M., see IINO, H., (3) 759
TURK, D. L., see AMBELANG, J. C., (4) 1186
TURNER, R. R., L. G. GAETA, A. G. ALTENAU, AND R. W. KOCH, Determination of carbon-bound lithium in polymer cements, (4) 1054

VAN DER WAL, C. W., see SCHWARZL, F. R., (2) 557
VAN KREVELEN, D. W., AND P. J. HOFTYZER, Practical evaluation of the [η]–M relationship. II. Estimation of K_θ values of polymer solutions, (2) 462
VITOLINS, G., Adhesion of chlorobutyl blends to highly unsaturated elastomers. III. Effect of mineral fillers, oil, and resin. (Abstract), (3) 971
VOET, A., A. K. SIRCAR, AND T. J. MULLENS, Electrical properties of stretched carbon black loaded vulcanizates (3) 874
——, see PAPIRER, E., (4) 1200

WAGNER, M. G., Mill behavior of elastomers: scale-up criteria (Abstract), (5) 1479
WALDROP, M. A., AND G. KRAUS Nuclear magnetic resonance study of the interaction of SBR with carbon black, (4) 1155
WARNER, W. C., see CAMPBELL, D. R., (1) 1
WARTMANN, H. J. The relative performance of silica and carbon black in natural rubber at comparable chemical crosslink levels (Abstract), (5) 1499
WATSON, A. A., see SKINNER, T. D. (2) 404
——, RUSSELL, R. M., (2) 418

WEI P. E., see REHNER, J., JR., (4) 985
WEISSBEIN, L., see SINGH, A., (2) 648
WEISSERT, F. C., Polymer structure and multispeed rheology, (3) 903
——, see ANDERSON J. N., (3) 918
WHITE, J. L., Elastomer rheology and processing (Review), (1) 257
——, Extrusion of polymer melts and melt flow instabilities. III. Theoretical analysis of extrusion through a slit die, (3) 691
——, see BIALAS G. A., (3) 675, 682
WHITTINGTON, L. E., see LEWIS, J. E., (3) 892
——, see CORMAN, B. G. (5) 1473
WILDER, C. R., see HAWS, J. R., (5) 1495
WILLIAMS, M. L. see KELLEY, F. N. (4), 1175
WILDER, C. R., see HAWS, J. R., (5) 1495
WILLIAMS, M. L., see KELLEY F. N., (4) 1175
WILLIAMS, R. J., AND R. W. A. HUDSON, Techniques for examination of high impact polystyrene by electron microscopy, (2) 641
WILSON F. H., JR., see AMBELANG, J. C., (4) 1186
WILSON, G. J., see OXLEY, C. E., (4) 1147
WIRTH, K. H., A new dimension in EPDM compounding (Abstract), (3) 977
WISE, R. W. see DEASON, W. R., (5) 1481
WOLSTENHOLME, W. E., (3) G 60
WONG, CHIU-PING, see LANGLEY, N. R., (5) 1277
WOODS, M. E. see GOSHORN, T. R., (5) 1478

YASUDA, G., see NINOMIYA, K., (3) 714
YOSHIMURA, N., AND K. FUJIMOTO, Structure of vulcanized and unvulcanized SBR/BR blends (4) 1009
——, see SEKIGUCHI, H., (2) 547
YOUNG, D. G., AND S. J. GOODSTEIN The effects of inner tube splicing process variables on uncured and cured splice strength (Abstract), (3) 973

SUBJECT INDEX

Abstracts, papers presented at Division of Rubber Chemistry meetings, (3) 956; (5) 1466
Abrasion, see also Carbon black
of rubber, effect of temperature, (4) 1087
effect of carbon black structure, (5) 1495
Adhesion, chlorobutyl to unsaturated elastomers, (3) 971
of elastomers, (1) 30
of elastomers to cords, (1) 159
of elastomers to glass, (1) 60
by resorcinol formaldehyde system, (1) 159
rubber to rubber, (5) 1480
of steel wire to rubber, (1) 183; (2) 613
test for, (5) 1486
Aging, effect on tack, (4) 1040
rubber vulcanizates and MBT, (3) 735
viscoelastic behavior of rubbers, (5) 1294
Allylic chloride, in epoxide rubber, (4) 1028
Analysis, of carbon lithium bonds in polymer cements, (4) 1054
of compounding ingredients, (2) 625
of crosslink type, (4) 1136; (5) 1412
of elastomers by gas chromatography, (5) 1350
of elastomers by radioisotopes, (1) 1; (5) 1277
Antioxidants, analysis, (2) 265
and fatigue, (4) 1095
migration of, (3) 892
phenolic, (5) 1466
Antiozonants, EPDM as, (3) 975; (4) 1186
extractability by water, (5) 1471
phenylenediamines as, (4) 1186
Apparatus, for adhesion, (5) 1480
for automatic stress relaxation measurement, (3) 835
for belt flex dynamic adhesion for tire cord, (1) 159
for compression adhesion test of tire cord, (1) 159
for compression extension test of tire cord, (1) 159
for dynamic flex adhesion for tire cord, (1) 159
for dynamic shear adhesion test for tire cord, (1) 159
for dynamic strip adhesion for tire cord, (1) 159
fiberglass fatigue tester, (5) 1491
microhardness tester, (5) 1483
oscillating disk rheometer, (5)
for retarded deformation, (2) 373
for roller flex adhesion for tire cord, (1) 159
for stress induced crystallization, (5) 1420
for rubber friction, (4) 1122; (5) 1433
for tack measurement, (4) 1040
for thermal conductivity of rubber, (5) 1314
for tirecord fatigue, (4) 1000
for tire cord tension in tires, (3) 812
Asphalt, reinforcement by elastomers, (5) 1476
Atmospheric attack on rubber, (4) 1095
Automation, electron microscope analysis, (4) 1209
strain rate measurement, (5) 1420

Benzothiazolinethione, and aging, (3) 735
in curative diffusion, (4) 1058
in efficient vulcanization, (2) 404
exchange with sulfur, (1) 1
identification in rubber, (2) 625
in injection molding recipes, (5) 1336
isotopically tagged, (3) 892
in mechanism of accelerated sulfur vulcanization, (5) 1366
Benzothiazolyl disulfide, containing radiosulfur, (1) 1; (3) 892
in curative diffusion, (4) 1058
in efficient vulcanization, (2) 404, 418
identification in rubber, (2) 625
in mechanism of accelerated sulfur vulcanization, (5) 1366
radioactive in migration study, (3) 892
Bevilacqua, Edward M., Obituary, (1) G28
Birefringence, temperature dependence and rubber orientation, (2) 509
Biographical sketches and obituaries, Bevilacqua, E. M., (1) G28
Gregg, E. C., Jr., (2) G55
Mooney, M., (3) G60
Rogers, T. H., (1) G4
Thomas, R. M., (4) G87
Blends, of carboxy SBR and vinylpyridine SBR, (3) 759
chlorobutyl and unsaturated rubbers, (4) 985
differential thermal analysis, (1) 110
heterogeneity and crosslinking, (4) 985
SBR/BR structure of, (4) 1009
Block polymers, stress softening, (3) 956
viscoelestic and ultimate tensile properties of SBS, (5) 1257
Book reviews, Addition Polymers: Formation and Characterization, (4) G79
Autooxidation of Hydrocarbons and Polyolefins, (4) G76
Carbanions, Living Polymers, and Electron Transfer Processes, (4) G76
Computer Programs for Plastics Engineers, (4) G79
Development and Use of Polyester Products, (5) G102
Diffusion Controlled Stress Relaxation of Swollen Rubber Like Networks (5) G103
Elasticity and Structure of Polyurethan Networks, (5) G103
Ethylene and Its Industrial Derivatives, (5) G103
Handbook of Ocean and Underwater Engineering, (5) G102
Markets for Plastics, (4) G76
Monoolefins, Chemistry and Technology, (5) G102
Organic Accelerators in the Vulcanization of Rubber, (4) G78
Plastics Rheology: Mechanical Behavior of Solid and Liquid Polymers, (4) G78
Physical Methods in Macromolecular Chemistry, (5) G102
Polyurethan Technology, (4) G77
Polyvinyl Chloride, (4) G77
Stabilization of Polymers and Stabilization Processes: Advances in Chemistry Series 85, (5) G102
Statistical Mechanics of Chain Molecules, (4) G75
Testing of Polymers, Vol. 4, (4) G77
Structure and Mechanism in Vinyl Polymerization, (5) G102
Bound rubber, (3) 850, 858
Bulk friction, (4) 1122
Butyl rubber, adhesion, (1) 30
bound rubber and carbon black, (5) 1494
critical surface tension of spreading, (1) 30
curative diffusion in, (4) 1058
differential thermal analysis, (1) 110; (5) 1490
equation of state for, (5) 1399
friction, (4) 1122
interaction with carbon black, (3) 850, 858
isoprene structure in, (2) 392
nuclear magnetic resonance, (2) 392
peroxide curing, (4) 1147
thermal conductivity of black filled, (5) 1314
thermal gravimetric analysis, (5) 1490
thermodynamics of mixing, (5) 1397
Bylaws of the Division of Rubber Chemistry, (1) G16
changes in, (5) G102

Calendar of Technical Meetings, (1) G6; (4) G80
Carbon black, aggregates, (4) 1209; (5) 1496
analysis by TGA, (5) 1490
bound rubber and, (3) 850, 858; (5) 1494
effect on diffusion of oil, (5) 1473
effect of dispersion on tread performance, (3) 700
effect on injection molding, (5) 1321, 1336
effect of milling on structure, (5) 1493
effect of structure on wear, (5) 1495
effect of structure on tread performance, (3) 700
influence on swelling rate, (2) 604
labeled hydrogen in, (4) 1200
microstructure, (4) 1209
morphology, (4) 1209; (5) 1496
structure and vulcanizate properties, (2) 598
Catalyst, for copolymerization of propylene oxide, (4) 1028
for ethylene, propylene, and dicyclopentadiene terpolymerization, (2) 363, 368
metallic for oxidation of SBR, (5) 1468
Cement, lithium in polymer, (4) 1054
Chain stiffness, per main chain atom, (2) 462
backbone, (4) 1175
Chlorobutyl rubber, adhesion, (3) 971
in elastomer blends, (4) 985
Chlorosulfonated polyethylene, critical surface tension of spreading, (1) 30
identification of compounding ingredients in, (2) 625
stability, (1) 110
Chromatography, analysis of tread rubbers, (5) 1350
gel permation, calibration, (2) 636
thin layer for identification of organic compounds in vulcanizates, (2) 625
Coagulation, effect on properties of SBR black masterbatch, (3) 957
Compatibility of polymers, (2) 447
Compliance, and chain scission, (5) 1501
complex shear, (4) 1277
creep, (2) 557
equilibrium, (4) 1175
equilibrium shear, (4) 1285
flow, (3) 903
shear creep, (5) 1501
storage, (4) 1277
Compressibility, of polyisobutylene, (5) 1409
Compression set, low of fluorocarbon elastomers, (5) 1503
Compression stress strain, natural rubber, (2) 580
Computer, curing by program for, (5) 1481
physical testing of rubber by, (5) 1482
Conductivity, thermal of butyl rubber, (5) 1314
electrical of SBR, (3) 874
Constant, K_θ, list for polymers for viscosity measurement, (2) 462
solvent and polymer interaction, (5) 1397
Cord, adhesion to rubber, (1) 159
compression, (4) 1000
fatigue tester, (4) 1000
fiberglass, (5) 1491
in hose design, (3) 666
path and tire contour, (4) 1034
steel, adhesion to rubber, (2) 613
tension in tires, (3) 812
in tire expansion, (4) 1079
Cornering, slip angle in, (4) 1014
Crack growth, in tires, (5) 1462
Cracking, effect of EPDM on, (3) 975
fatigue in polybutadiene, (4) 1095
function of black structure, (3) 700
function of sulfur content, (3) 700
ozone, (4) 1186
tires, (5) 1462
Creep, see also Relaxation, Stress relaxation, Retarded deformation
chain scission contribution to, (5) 1501
compliance, (2) 557
compression, (3) 903
under large tensile stresses, (2) 557
of polybutadiene, (4) 1095
of polyether urethan, (4) 1095
of polyvinyl chloride, (2) 373
shear compliance, (5) 1501
Critical surface tension of spreading, (1) 30
Crosslink density, from compression modulus of swollen vulcanizates, (2) 580
constant at variable accelerator to sulfur ratio, (3) 969
distribution, (3) 659
effect on diffusion coefficient, (2) 495
and entanglement in EPDM, (4) 1167
in EV systems, (2) 404, 418
extraction of low molecular weight material, (2) 471; (4) 1136
Flory and Rehner equation, (3) 744
influence of carbon black, (2) 604
and main chain rupture, (2) 505
micromethod for estimation, (2) 580
of peroxide curing in presence of sulfur, (3) 744
polybutadiene, (4) 1136
in polymer engineering, (4) 1175
of swollen rubber in compression, (2) 589
variation with methyl halide reaction, (4) 1136
Crosslink, efficiency of, (2) 404, 418; (5) 1245
Crosslink scission, during aging, (3) 924
contribution to creep, (5) 1501
Crosslink structure, (4) 1136
effect on tensile strength and oxygen absorption, (5) 1412
Crosslinking, see also Aging, Swelling, and Vulcanization
Crystallization, in block copolymer, (5) 1257
kinetics of polybutadiene, (2) 535
measurement of, (1) 110
and mechanical history, (2) 530
of natural rubber, (2) 540
polymer history of, (3) 769
of cis polypentenamer, (5) 1235
and stark rubber, (2) 540
stress induced in natural rubber, (5) 1420
Cure, see Vulcanization
Cut growth, in tires, (5) 1462
Cyclopentene, polymerization, (5) 1235

Deborah number, (5) 1479
Degradation, see also Aging, Oxidation, crosslink scission, (3) 924
and failure behavior, (4) 1095
mechanical in rheology, (5) 1294
by methyl halides, (4) 1136
of urethans, (2) 648
zinc compounds during, (3) 735
Density, equation of change with temperature for polyisobutylene, (5) 1409
Devulcanization, with methyl halides, (4) 1136
Dicyclopentadiene, termonomer of EPDM, (2) 363, 368
Differential thermal analysis, (1) 110
Diffusion, and adhesion, (1) 53
of curatives, (4) 1058
of n-hexadecane in natural rubber, (5) 1277
of liquids in crosslinked rubbers, (2) 495
of oil in rubber, (2) 474
radioisotope study, (1) 1
tracer studies of, (2) 481
Dilatometry, of polyisobutylene, (5) 1397
Dispersion, of elastomers in blends, (4) 985
Distribution of network chains, (3) 659; (5) 1277
Disulfides, in rubber vulcanizates, (5) 1412
Division of Rubber Chemistry, bylaws, (1) G16
bylaws changes, (5) G101
committees, (2) G35
future meetings, (1) G4; (2) G44; (3) G58; (4) G66; (5) G99
library information service, (1) G2; (2) G34; (3) G58; (4) G66; (5) G99
officers and executive committee, (1) G1; (2) G33; (3) G57; (4) G65; (5) G98
program for Fall meeting, 1969, (4) G84
program for Spring meeting, 1969, (2) G46
Dynamic properties, of aging elastomers, (5) 1501
at glass transition temperatures, (2) 557
and microstructure, (4) 1175

of oil extended rubber, (5) 1277
of PVC, (2) 373
of SBR filled with glass beads, (5) 1498

Elasticity theory, (2) 441, 580, 589; (3) 835; (4) 1167, 1175; (5) 1277, 1285, 1501
Elastomers, see also specific polymers, adhesion, (1) 30
deformation softening, (1) 339
engineering of, (4) 1175
radioisotope analysis, (1) 1
rheology and processing, (1) 257
thermodynamics, (2) 441; (5) 1397, 1409; (3) 835
Electron microscope, carbon black study with, (4) 1209
study of high impact polystyrene, (2) 641
Electron spin resonance, (4) 1155
Engineering of polymers, (4) 1175
Entanglement, and chemical crosslinks, (4) 1167
in EPDM, (4) 1167
natural rubber, (4) 1167
cis polybutadiene, (4) 1136, 1167
SBR, (4) 1167
trapped, (5) 1277
Entanglement flow, (5) 1294
Enthalpy of mixing, (5) 1397
Epichlorohydrin rubber, (3) 964
melt viscosity, (3) 790
rheological behavior, (5) 1487
Epoxide rubber, (4) 1028
adhesion to tire cords with, (1) 159
Equation of state of polyisobutylene, (5) 1409
Ethylene propylene rubbers, as antiozonants, (3) 975; (4) 1136
autohesion, (5) 1480
compounding, (3) 977
critical surface tension of spreading, (1) 30
differential thermal analysis, (1) 110
diffusion of curatives in, (4) 1058
flow and rheology, (2) 682
hose, (3) 980
injection molding of, (5) 1321, 1336
migration of extender oil in, (5) 1473
mill behavior and its scale up, (5) 1479
oil for, (5) 1474
orientation birefringence, (2) 509
peroxide curing, (5) 1245
tack improvement, (3) 966
tack measurement, (4) 1040
Extraction, of oil from natural rubber, (5) 1277
of polyisoprene, (2) 471
Extrusion, mathematical model, (3) 780
plasticating screw, (3) 780
of polymer melts, (3) 675, 682, 691
slit die, (3) 691

Failure, see also Aging, Antiozonants, Cracking, Cut growth, Fatigue
adhesional, (1) 30
envelope, (5) 1267
of polybutadiene, (4) 1095
of polyurethans, (2) 648
Fatigue, see also Cracking, Cut growth, estimate of life, (4) 1175
fiberglass testing for, (5) 1491
of polybutadiene, (4) 1095
of tire cord, (4) 1000
of tire cord adhesion, (1) 159
Fiberglass, fatigue testing of, (5) 1491
adhesion, (1) 159
Fillers, chemical interaction with polymers, (3) 850, 858; (5) 1494
determination of content by TGA, (1) 110; (5) 1490
effect on die swell, (3) 957
effect of dispersion on SBR masterbatch, (3) 957
effect on injection molding of EPDM, (5) 1321, 1336
effect of milling on structure, (5) 1493
effect on rheological properties, (1) 257
effect on shear in glassy region, (2) 557
effect of structure on vulcanizate properties, (2) 598
effect of surface, structure, and dispersion on tread performance, (3) 700; (5) 1495
effect on swelling rate, (2) 604
effect on T_g, (1) 110
and hydrogen transfer, (4) 1200
NMR study of interaction with SBR, (4) 1155
softening of vulcanizates containing, (1) 339
Flatspotting, mechanism of, (1) 159
Flow, see also Rheology, Extrusion, entanglement, (5) 1294
epichlorohydrin rubber, (3) 790; (5) 1487
and injection molding, (3) 959; (5) 1321, 1336
instability of polymer, (3) 675, 682
and mechanical degradation, (5) 1294
melt flow, (1) 257; (3) 675, 682, 691, 823
and molecular branching, (3) 823; (5) 1294
and molecular weight, (3) 823
and polymer structure, (3) 903
transient and steady, (3) 714
unstable, (1) 257
Fluorocarbon rubbers, aerospace seals, (5) 1502
critical surface tension of spreading, (1) 30
for low compression set, (5) 1503
Free radicals, in aging of vulcanizates, (3) 924
in carbon black, (4) 1200
mechanisms for carboxyl terminated polybutadiene, (1) 71
in peroxide vulcanization, (5) 1245
in peroxide sulfur vulcanization, (3) 744
in peroxide vulcanization of butyl, (4) 1147
in sulfur vulcanization reactions, (5) 1366
during tensile break, (2) 505
Freezing point, see also Differential thermal analysis
cis polypentenamer, (5) 1235
Friction, bulk, (4) 1122
rubber deformation losses in, (4) 1122
sliding, (5) 1433
surface, (4) 1122

Gas chromatography, in analysis of treads, (5) 1350
Gel permeation chromatography, (2) 636
Glass, beads as filler, (5) 1498
to elastomer adhesion, (1) 30
fiber fatigue test, (5) 1491
fiber tire cord, (1) 159
fiber tire cord adhesion, (1) 159
Glassy state, of unfilled and filled rubber, (1) 110; (2) 557
of polypentenamer, (5) 1235
Goodyear, Charles, medalist, Robert M. Thomas, (4) G90
Gordon research conferences, 1969, (2) G49
Gregg, Earl C., Jr., biographical sketch, (2) G55
Guide for authors, (1) G11

Hardness, microtester for, (5) 1483
Helmholtz free energy, (2) 589
High, speed strain, (5) 1420
impact polystyrene, (2) 641
pressure osmometry, (5) 1397
Hose, design principles, (3) 666
equipment for making, (3) 983
EPDM rubber for making, (3) 980
fibers in, (3) 982
future of, (3) 982
polymers for, (3) 982
performance, (3) 983
manufacture in Europe, (3) 984
Hydrogen, abstraction in peroxide crosslinking, (5) 1245
evolution during tensile break of rubber, (2) 505
transfer between carbon black and rubber, (4) 1200
Hydroquinone, curing agents for fluorocarbon rubbers, (5) 1503
Hypalon, see Chlorosulfonated polyethylene

Identification, see Analysis
Impact, high, polystyrene, (2) 641
high velocity transverse, (2) 565
Information retrieval, (5) 1490

Infrared spectrum, polychloroprene, (2) 394
Injection molding, (3) 959, 961
  effect of oil and black on, (5) 1321, 1336
Instruments, see Apparatus
Integral, for flow of viscoelastic materials, (1) 257; (3) 691
  for lateral tire force, (4) 1014
  for stress relaxation of elastic component, (3) 714
  tire contour for arbitrary cord path, (4) 1034
Internal energy, of natural rubber, (3) 835
  and rubber elasticity, (3) 835
Isomerism, rotational, (5) 1383
Intrinsic viscosity, (2) 463
Isocyanates, in tire cord adhesion, (1) 159
Isomers, conformation models of polyisoprene, (5) 1383
Isoprene, configuration in butyl rubber, (2) 392

Kinetics, accelerated vulcanization, (5) 1366
  of crosslink scission, (4) 1136
  of crystallization, (2) 530, 540
  of polymer degradation, (1) 110

Latex, polyvinyl chloride as cord dip, (1) 159
Lithium, organo as initiator, (2) 520
  in polymer cements, (4) 1054
Loss modulus, (4) 1175

Mark and Houwink relation, (2) 462
Masterbatch, black dispersion and, (4) 957
MBT, see Benzothiazolinethione
MBTS, see Benzothiazyl disulfide
Mechanism, of cord fatigue, (1) 159
  of flatspotting, (1) 159
  of peroxide and MBT reactions in vulcanization, (3) 744
  of reaction of methyl iodide with monosulfides, (4) 1136
  of reaction of peroxide and sulfur in vulcanization, (3) 744
  of vulcanization, (5) 1366
Meetings, Division of Rubber Chemistry, (2) G46; (4) G84
Melting, see also Crystallization, and birefringence, (2) 509
  in block copolymers, (2) 520
  of polybutadiene, (2) 530
  of cis polypentenamer, (5) 1235
  of stark rubber, (2) 540
Mercaptobenzothiazole, see Benzothiazolinethione
Metal ions, catalysts for oxidations of SBR, (5) 1468
Methyl bromide, in crosslink scission, (4) 1136
Methyl iodide, in crosslink scission, (4) 1136
Methyl methacrylate, block copolymers with styrene, (2) 447
Methyl butenes, models of configuration of polyisoprene, (5) 1383
Methyl pentenes, models of configuration of polyisoprene, (5) 1383
Microinterferometry, measurement of curative diffusion by, (4) 1058
Microscope, for diffusion measurement, (4) 1058
Microstructure, see also Carbon black, individual polymers
  of block copolymers, (2) 520
  of carboxy terminated polybutadienes, (3) 800
  effect on rheological properties of EPDM, (3) 944
  of telechelic polybutadiene, (1) 71
  in tread rubbers, (5) 1350
Milling, effect on carbon black structure, (5) 1493
  scale up of, elastomeric behavior during, (5) 1479
Mixing, (5) 1397, 1492, 1493
Molecular weight distribution, (4) 1136; (2) 636
Molecular structure, and flow behavior, (3) 823
Mooney, Melvin, (3) G60
Mooney and Rivlin constants, variation with strain rate, (5) 1420
Morphology, of carbon black, (4) 1209
  of carbon black aggregates, (5) 1496
  of polyethylene and chlorinated polyethers, (3) 769
  of styrene butadiene styrene copolymers, (5) 1257
Mossbauer effect, (1) 24
Mullins effect, (1) 339
Multispeed rheology, (3) 903

Natural rubber, see also Polyisoprene, abrasion resistance, (4) 1087
  adhesion to steel wire, (2) 613
  and carbon black structure, (3) 858
  complex shear compliance, (5) 1277
  compression set, (2) 589
  compression stress strain, (2) 580
  cracks in, (4) 1186
  critical surface tension of spreading, (1) 30
  diffusion of curatives in, (4) 1058
  diffusion of liquids in, (2) 495
  diffusion of oil in, (5) 1473
  effect of crosslink structure on oxygen absorption and tensile strength of, (5) 1412
  effect of network breakdown on swelling in compression, (2) 589
  efficient vulcanization of, (2) 404, 418
  fatigue properties, (2) 418
  friction of, (4) 1122
  hydrogen evolution at tensile break, (2) 505
  internal energy of, (3) 835
  kinetics of crystallization, (2) 540
  oil extended, (5) 1277
  ozone crack initiation, (4) 1186
  phenolic antioxidants in, (5) 1466
  plasticity, (2) 381
  Poisson ratio, (2) 547
  pyrolysis of, (5) 1350
  reinforcement by silica, (5) 1499
  resilience change upon aging of, (2) 381
  storage compliance, (5) 1277
  strain wave propagation, (2) 565
  stress induced crystallization, (5) 1420
  stress softening, (1) 339
  swelling in compression, (2) 589
  tack measurement of, (4) 1040
Neoprene, see Polychloroprene
Network, chain distribution, (3) 659; (5) 1285
  elastically effective strand density of, (5) 1285
New publications, see also New Books, (1) G27; (2) G54
New Books, see also Book reviews, (4) G75; (5) G102
Nitrile rubber, adhesion, (1) 30
  adhesion to tire cord of various compositions, (1) 159
  critical surface tension of spreading, (1) 30
  EPR as antiozonants for, (3) 975
  functionally terminated, (1) 71
  in hose manufacture, (3) 982
  powdered, (5) 1478
  processing of powdered, (5) 1478
  rheology of, (3) 790; (5) 1487
  stress and strain behavior of swollen networks, (2) 572
  tack improvement, (3) 966
  vulcanization of, (5) 1468
Nuclear magnetic resonance, isoprene structure in butyl by, (3) 392
  study of carbon black and SBR interaction by, (4) 1155
Nylon, adhesion to, (1) 159
  critical surface tension of spreading, (1) 30
  flow, (2) 682
  heat aging resistance of, (1) 159
  manufacture of yarn, (1) 159
  mechanism of cord fatigue, (1) 159
  mechanism of flatspotting, (1) 159
  reduced flatspotting, (1) 159
  shear, compression, elongation, and flex of, (4) 1000
  shear stress and shear rate of (2) 675
  strength loss in tire curing, (1) 159

Oil, effect on adhesion of chlorobutyl rubber, (3) 971
  effect on DTA and TGA, (1) 110
  effect on entanglement in natural rubber, (5) 1277

effect on injection molding, (5) 1321, 1336
effect on low frequency losses in rubber, (5) 1277
effect on properties of injection molded rubber, (5) 1336
effect on rheology of elastomers, (1) 257
effect on shear rate of rubber, (5) 1321, 1336
extender, migration of, (2) 474; (5) 1277, 1473
and processibility, (3) 714
radioisotope analysis, (1) 1
requirements for EPDM rubbers, (5) 1474
Optical effects and crystallinity, (2) 509
effects and curative diffusion, (4) 1058
Oxidation of SBR, (5) 1468
Oxidative aging, resistance to thermal, (2) 418
Oxygen, effect on peroxide crosslinking, (5) 1245
effect on vulcanized natural rubber, (3) 933
influence of crosslink structure on absorption of, (5) 1412
in oxidation of SBR, (5) 1468
in polybutadiene failure, (4) 1095
Ozone, crack initiation, (4) 1186
in polybutadiene failure, (4) 1095

Peroxide, crosslinking of unsaturated polyolefins, (5) 1245
in curing butyl rubber, (4) 1147
in curing EPDM, (4) 1167
effect of carbon black and silica on vulcanization of rubber by, (5) 1499
effect on main chain scission, (3) 927
in mechanism of crosslink scission, (3) 927
for preparation of sulfoxides, (3) 927
vulcanization of rubber in presence of sulfur, (3) 744
Phenylenediamines as antiozonants, (5) 1471
Phenyllithium, chemical probe for polysulfide and disulfide crosslinks, (4) 1136
Physics of slipping wheel, (4) 1014
Pico test, effect of temperature, (4) 1087
Plasticity retention index (PRI), (2) 381
Poisson's ratio, of natural rubber, (2) 547
Polybutadiene, and bound rubber, (3) 858
critical surface tension of spreading, (1) 30
crystallization, (2) 530
diffusion of curatives, (4) 1058
failure behavior, (4) 1095
functionally terminated, (1) 71; (3) 800
migration of extender oil in, (5) 1473
oxidative aging, (4) 1095
peroxide vulcanization, (5) 1245
processing, (3) 714
pyrolysis, (5) 1350
rheology of, (1) 257; (2) 682; (5) 1294
sulfur crosslinks in, (4) 1136
telechelic, (1) 71
tire cord adhesion, (1) 159
viscosity of carboxy terminated, (3) 800
viscosity and molecular weight, (2) 462
Polychloroprene, allylic chlorine in, (4) 1028
critical surface tension of spreading, (1) 30
differential thermal analysis, (1) 110
functionally terminated, (1) 71
infrared spectrum, (3) 394
injection molding of, (3) 959
polyisocyanate curing of, (2) 394
rheology of, (3) 790
in reinforcement of asphalt and tar, (5) 1476
tire cord bonding, (1) 159
viscosity and molecular weight, (2) 462
Polydimethylsiloxane, birefringence, (2) 509
Polyethers, chlorinated, (3) 769
Polyethylene, adhesion, (1) 30
critical surface tension of spreading, (1) 30
crystallization, (3) 769
differential thermal analysis, (1) 110
extrusion, (3) 780
flow and extrusion, (3) 675, 682, 823
functionally terminated, (1) 71
morphology of, (3) 769
orientation birefringence, (2) 509
viscosity and molecular weight, (2) 462
Polyethylene terephthalate, adhesion, (1) 30
adhesion to rubber, (1) 159
manufacture, (1) 159
physical properties, (1) 159; (4) 1000
tire cord, (1) 159
viscosity and molecular weight
Polyfluorotriazines, (3) 963
Polyisobutylene, see also Butyl rubber, adhesion, (1) 30
backbone stiffness, (4) 1075
and bound rubber, (3) 858
density change with temperature, equation for, (5) 1409
equation of state, (5) 1409
functionally terminated, (1) 71
thermal expansion coefficient, (5) 1409
thermal pressure coefficient, (5) 1409
thermodynamics of mixing, (5) 1397
Polyisocyanate, cure of polychloroprene with, (2) 394
Polyisoprene, see also Natural rubber, analysis by gas chromatography, (5) 1350
backbone stiffness, (4) 1075
critical surface tension of spreading, (1) 30
functionally terminated, (1) 71
injection molding of, (3) 961
mechanical degradation, effect on rheology of, (5) 1294
processing, (3) 714
rheology of, (1) 257; (5) 1294
vibrational and rotational isomerism, (5) 1383
viscosity and molecular weight.
Polymerization of ethylene, propylene, and dicyclopentadiene, (2) 363, 368
Polymethylmethacrylate, compatibility, (2) 447
flow and rheology, (3) 682
Polypentenamer, (5) 1235
Polypropylene, mechanical properties, (3) 769
Polystyrene, compatibility, (2) 447
critical surface tension of spreading, (1) 30
flow and rheology, (3) 675
gel permeation chromatography, (2) 636
glass transition, (2) 520
high impact and electron microscopy, (2) 641
viscosity and molecular weight, (2) 462
Polysulfide crosslinks, and breaking strength of vulcanizates, (5) 1412
isotope exchange with sulfur, (1) 1
and methyl halide cleavage, (4) 1136
and oxidative aging, (3) 924
phenyllithium cleavage of, (4) 1136
Polyurethans, improved low temperature and water resistances, (5) 1502
in shear at glass transition temperatures, (2) 557
thermal stability of, (2) 648
viscosity and molecular weight, (2) 462
Polyvinyl chloride, critical surface tension of spreading, (1) 30
flow and rheology, (3) 682
latex as cord dip, (1) 159
stress relaxation, (2) 373
viscoelastic response to large deformation, (2) 373
Post cure inflation, (3) 812
Pressure, of contact in tack, (4) 1040
effect on shear rate of rubber, (5) 1321, 1336
thermal coefficient of, for polyisobutylene, (5) 1409
Processibility of rubber, (3) 714
Pyrolysis, in analysis of tread rubbers, (5) 1350
of natural rubber, polybutadiene, and SBR, (5) 1350
of SBR, (4) 1200

Radiation crosslinking, (2) 509
Radical and polar mechanisms in vulcanization, (3) 744; (5) 1366
Radioisotope analysis, (1) 1
Refractive index and crystallinity, (2) 509
of rubbers, (4) 1058
Reinforcement, of asphalt and tar, (5) 1476
braid for hose, (3) 666
loom for hose, (3) 666
ply for hose, (3) 666
mechanism of carbon black, (4) 1200
of rubber by carbon black, (2) 557, 598, 604; (3) 700, 850, 858, 874, 936, 957, 969;

(4) 1155, 1200, 1209; (5) 1314, 1321, 1336, 1494, 1495, 1496, 1499.
Relaxation rate, styrene butadiene styrene block copolymers, (5) 1257
Relaxation time, nuclear spin lattice, (4) 1155
of polymers, (4) 1175
Resilience, change with aging of natural rubber, (2) 381
as a function of temperature, (2) 381
as a function of aggregate size of carbon black, (4) 1209
Rheology, continuum theory of, (1) 257
of elastomers, (1) 257
of epichlorohydrin rubber, (3) 790; (5) 1487
and extrusion, (1) 257
and internal mixer, (1) 257
of rubber, effect of mechanical degradation on, (5) 1294
and rubber mill, (1) 257
Rogers, Thomas H., Jr., biographical sketch, (1) G2
Rosin gum, for building tack, (3) 966
Rubber, bound, (5) 1494
friction, (4) 1122; (5) 1433
physical testing, (5) 1485
powdered, (5) 1478
prediction of properties, (5) 1469, 1498
to rubber adhesion, (5) 1480
viscoelastic behavior on aging, (5) 1501
Rubber groups, officers and meeting dates, (1) G3; (2) G38; (4) G68

Scission, chain in polybutadiene, (4) 1095
crosslink in polybutadiene, (4) 1136
rate of, (4) 1136
Shear, compliance, complex for natural rubber, (5) 1277
critical rate, (5) 1294
degradation of rubbers by, (5) 1294
force, in glassy state, (2) 557
during milling, (4) 985
modulus of polyurethans, (2) 557
rate of, (5) 1294, 1321, 1336
rate and injection molding, (5) 1321, 1336
stress and flow behavior, (3) 823
Silica, performance relative to carbon black as reinforcing material, (3) 971; (5) 1499
Slip, physics of, (4) 1014
Sodium chloride, as filler for polyurethan, (2) 587
Softening of natural rubber by deformation, (1) 339
Splice inner tube process, (3) 973
Stark rubber, (2) 540
Strain, amplification factor, (1) 352
behavior in swollen network, (2) 572
rate measurement, (5) 1420
velocity, (2) 565
wave in natural rubber, (2) 565
Strength of vulcanizates, effect of network chains, (3) 659
Stress, behavior in swollen networks, (2) 572
relaxation, and aging, (5) 1501
of ethylene propylene rubbers, (3) 944
of natural rubber, (1) 339
of polybutadiene, (4) 1095
of polyurethans, (2) 648
of polyvinyl chloride, (2) 373
and processing, (2) 714
and rheology, (1) 257
softening, of block polymers, (3) 956
of natural rubber, (1) 339
Styrene butadiene rubber, abrasion resistance as a function of carbon black parameters, (3) 700; (5) 1495
adhesion, (1) 30
adhesion of chlorobutyl, (3) 971
adhesion of tire cords, (1) 159
antiozonants in, (5) 1471
autohesion, (5) 1480
and black masterbatch, (3) 957
blends of carboxy and vinylpyridine, (3) 759
block, (5) 1257
and bound rubber, (3) 858
building tack of, (3) 966
carboxy terminated, (3) 759; (1) 71
coagulation of black masterbatch, (3) 957
cracks in, (4) 1186
critical surface tension of spreading, (1) 30
crosslinking by peroxide, (5) 1245
curative diffusion in, (4) 1058
die swell of black filled, (3) 957; (5) 1496
differential thermal analysis, (1) 110
diffusion of antioxidants and accelerators, (3) 892; (4) 1058
diffusion of oil in, (5) 1473
dynamic properties, (2) 520
effect of carbon black on electrical conductance of, (3) 874
effect of milling black in, (5) 1493
EPDM as antiozonant in, (3) 975
friction of, (5) 1433
functionally terminated, (1) 71; (3) 759
hydrogen exchange with black, (4) 1200
influence of carbon black on swelling rate of, (2) 604
NMR study of black interaction with, (4) 1155
oil migration in, (2) 474; (5) 1473
oxidation catalyzed by metallic ions, (5) 1468
ozone cracking in, (4) 1186
peroxide crosslinking, (5) 1245
prediction of properties of filled, (5) 1498
processibility, (3) 714
pyrolysis of, (4) 1200; (5) 1350
random and block copolymers of, (2) 520
reinforcement of asphalt and tar by, (5) 1476
rheology, (1) 257; (5) 1487
rubber filler interaction, (3) 936
stress softening of crosslinked blocked, (3) 956
structure of, (4) 1009
tack and stick of, (4) 1040
thermal analysis, (3) 918
ultimate tensile of block copolymers of, (5) 1257
viscoelasticity and tensile of, (5) 1257
Sulfenamide, acceleration of natural rubber, (3) 969
Sulfur crosslinks, monosulfide in polybutadiene, (4) 1136
polysulfide in natural rubber, (5) 1412
scission of, (4) 1136
Surface tensions, critical spreading of polymers, (1) 30
Swelling, die of filled rubber, (3) 957
effect of carbon black on rate of, (2) 604
of rubber networks, network breakdown and reformation, (2) 589

Tack, apparatus for measuring, (4) 1040
building of rubber compounds, (3) 966
Tar, reinforcement by elastomers, (5) 1476
Tel-Tak, (4) 1040
Tensile, ultimate of styrene butadiene styrene block copolymers, (5) 1257
Tetramethylthiuram disulfide, efficient vulcanization, (2) 418
Tetraphenyltin, crosslinking agent for triazine elastomers, (5) 963
Thermal, conductivity, apparatus for measuring rubber, (5) 1314
expansion coefficient of polyisobutylene, (5) 1409
gravimetric analysis, (1) 110; (5) 1490
Thermodynamics, for elastomers, (2) 441, 589; (3) 835; (5) 1397, 1409
of mixing of alkanes with polyisobutylene, (5) 1397
Thermoelastic behavior of natural rubber, (3) 835
Tire, contour integral, (4) 1034
cord, adhesion of, (1) 159
fatigue tester, (4) 1000
tension in tires, (3) 812
crown angles, (4) 1079
cut growth, (5) 1462
design computation, (4) 1079
expansion rule, (4) 1079
grading system, (5) 1446
inflation tension, (3) 812
speed capability test for, (5) 1450
wear and force variation, (5) 1485
Topology, network and low frequency losses, (5) 1277

Tread wear, as function of carbon black aggregates, (4) 1209
as function of speed, (5) 1450
Triazine, thermally stable elastomer, (3) 963
Tritium labeled compounds, (4) 1200

Viscoelasticity at large deformations, (2) 373
Viscometer, Mooney, in rubber processibility, (3) 714
Viscosity and molecular weight, (2) 462
Vulcanization of rubber, development of MBT and zinc compounds of MBT during, (3) 735
efficient, (2) 404, 418
kinetics of accelerated, (5) 1366
mechanism, (5) 1366
nitrile rubber, (5) 1468
by peroxide, (3) 744; (5) 1245
programmed temperature of, (5) 1481
of cis polypentenamer, (5) 1235
profile, (3) 968
by radiation, (2) 509
radical and polar mechanisms in, (3) 744; (5) 1366
sulfur, peroxide, and accelerator combination in, (3) 744

Water, extraction of antiozonants by, (5) 1471
Wheel, physics of slipping, (4) 1014

Zinc compounds with mercaptobenzothiazole, in rubber aging, (3) 735
in vulcanization mechanism, (5) 1366

ADVERTISE *in*

RUBBER CHEMISTRY AND TECHNOLOGY

KEEP YOUR NAME AND YOUR PRODUCTS CONSTANTLY BEFORE THE RUBBER TECHNOLOGIST

Advertising rates and information about available locations may be obtained from

R. S. GRAFF, *Advertising Manager*
co University of Akron, Box 123
Akron, Ohio 44304